

Ex-160

Powered by 4x



Suitable for use in Zone 0 area
UL, ATEX and IECEx



Magnetic switch to prevent battery drainage in transport or to lock light on

Gas pressure release valve



Fastener prevents opening in hazardous places

- Intrinsically safe LED head torch for use in Zone 0 hazardous areas
- 160 Lumens light output
- Durable impact resistant light
- CREE XP-G
- Waterproof up to 1m (IP67)
- Powered by 4x AA Cell batteries

+ Optional extras:
• Helmet clip

Certification

UL	CLASS I DIV 1 GRP ABCD CLASS II DIV 1 GRP EFG CLASS III TEMP CODE: T4
ATEX	Ex: II 1 G Ex ia IIC T4 IP67
IECEX	Ex ia IIC T4 Ga IP67
Reach	Approved
RoHS	Approved
CE	Approved

Specifications Ex-160

Light Output	160 65 Lumens
Beam distance	120m 65m
Battery	4x Alkaline AA
Runtime	6hrs high 13hrs low
LED	CREE XP-G
Light Settings	High and low light settings
Dimensions	(L) 172mm (Dia.) 47mm
Product Weight	140g product weight excluding batteries
Battery Weight	23g weight per battery
IP Rating	IP67
Impact resistance	Impact resistant up to 1m
Part No.	NSEX160