# 690 Oil Resistant





#### RECOMMENDED FOR THESE RISKS:

Grip

Chemical protection

RECOMMENDED FOR THESE LINES OF WORK:

Automotive

Maritime sector

Metallurgy

## **Finer Filters Limited**

Unit 14 Gateway Business Centre Knockgriffin Midleton Co. Cork

www.finerfilters.ie Phone: 021 463-8727

EC compliance certificate delivered by the notified body 0120

0120
SGS United Kingdom Ltd., Systems & Services certification202B Worle Parkway - Weston-super-Mare, BS22 6 WA - UK
SHOWA BEST GLOVE

0120

Tour Franklin - La Défense 8 - 92042 Paris La Défense Cedex - France Tel. +33 (0)1 55 62 14 20 - Fax +33 (0)1 55 62 14 29 info@showabestglove.eu - www.showabestglove.eu

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

# Cotton knit PVC coating

### DESCRIPTION

•

Fully coated, extra coating over entire hand

- · Extended bonded sleeve, elasticated border
- · Rough finish over entire surface
- · Antibacterial and anti-odour treatment
- · Special hydrocarbon treatment
- · Eyelet for ventilation and hanging
- Anatomical shape

#### BENEFITS

- A flexible, soft glove that absorbs perspiration, for ultra comfortable extended wear and with good mechanical resistance.
- Seals and protects the hand against chemicals while remaining flexible
- Impermeable for working in damp or greasy environments, enabling you to grip objects securely
- · Sleeve stays correctly adjusted
- · Surface provides tactile feel and better grip
- · Greater hygiene
- · Easy hang storage
- Designed for easy movement and continuous wear
- · No irritation by seams in contact with the skin
- Extended protection for the entire arm

#### **AVAILABLE SIZES**

8/M • 9/L • 10/XL • 11/XXL

LENGTH
Dependent on size, in mm (flat)
650

PACKAGING
Pairs per pack/box 10/60

COLOUR OF SUPPORT/COATING

Blue

THICKNESS in mm 1,30

## RECOMMENDATIONS FOR USE

- The size given corresponds to a well fitting glove
- The stated impermeability performance level (EN374-3) does not reflect the actual protection level at the place of work
- Do not use with chemicals other than those tested without prior trials
- Store away from light and humidity

CUTTING

0 1 2 3 4 5

**PUNCTURE** 

ABRASION 0 1 2 3 <u>4</u>

TEARING

 Rinse the gloves in running water before removing, using a neutral detergent if necessary





J - N-HEPTANE 0 1 2 <u>3</u> 4 5 6

K - CAUSTIC SODA 40%

L - SULPHURIC ACID 96

[ Updated 13/10/11 ]

